



Product Data Sheet



Xpert-60 Snow-Foam-Max

SINCE
1987

1 US Gal (3.785L)
Code: XP-90027

Snow-Foam Blanket

- **Foam Blanket TFR:** Dramatic effect, foaming blanket which clings to surfaces, enhancing cleaning action to break down and lift all heavy soiling, traffic film, dirt, grease and oils.
- **Very economical:** Can be pre-diluted with up to 20 parts water.
- **Paint & Trim Friendly:** Contains livery enhancers: Kind to paintwork, trim and vehicle signwriting. Will not mark or dull surfaces: totally safe cleaning action even with repeated use.
- **Environment Friendly:** The surfactant(s) contained in this preparation complies with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.



Directions for Use:

Snow-Foam Max should be applied from bottom up and allowed to dwell until foam breaks.

NB: Do not allow material to dry out on any surface or staining mat occur.

After use rinse away thoroughly with plenty of cold water.

In very hot weather we recommend surfaces being cleaned to be cooled by pre-spraying with cold water before application of cleaning solution

Application:

For optimum results/performance Snow Foam Max should be applied via a foaming lance/gun.

For Direct Chemical Feed Pressure washers:
Pre-Dilute with up-to 4 parts water, prior to applying directly through the chemical feed 1-6% ratio for the desired foam, cling level.

Application via a foaming lance canister:
Pre-dilute with up to 10 parts water, adjusting the chemical feed setting on the canister to the desired foam, cling level

Concept Chemicals & Coatings Ltd.
Windmill Lane Industrial Estate, Denton, Manchester, M34 3RB. ENGLAND. T: +44 (0)161 335 0213

Concept Chemicals EU Ltd.
The Gallery, 13 Bedford Row Limerick, V94 VY47 IRELAND



For additional information see relevant Safety Data Sheet.

Made in Great Britain

www.xpert-60.com